

## Enterprise HD IP Phone---Gigabit Color IP Phone UC924

UC924 is an innovative Gigabit Color IP Phone, 3.5" TFT-LCD with 480\*320 pixel. It supports up to 5-way conference. UC924 is optimized for executive use for major decision makers, administrative assistants and those working with bandwidth-intensive application on collocated PCs. The high-resolution TFT-LCD and HD Voice bring you the lifelike visual and audio experience.

IP Phone UC 924



# IP PHONE THE FUTURE

www.htek.com



## Phone Features

Up to 12 SIP accounts  
Call hold, mute, DND  
One-touch speed dial, hotline  
Call forward, call waiting, call transfer  
Redial, call return, auto answer, direct IP call  
5-way conferencing  
XML Browser, action URL/URI  
Group listening, SMS, emergency call  
Ring tone selection/provisioning  
Set date time automatically or manually  
Dial plan per account  
RTCP-XR (RFC3611), VQ-RTCPXR (RFC6035)

## Voice Codecs Features

HD voice, HD handset, HD speaker  
Codecs: iLBC, G.722, G.711 (A/μ), Opus  
GSM\_FR, G.723, G.729AB, G.726-32  
DTMF: In-band, RFC 2833, SIP INFO  
Full-duplex hands-free speakerphone with AEC  
VAD, AGC, CNG, AEC, PLC, AJB

## Directory

Local phonebook up to 1000 entries  
XML/LDAP remote phonebook  
Intelligent search method  
Phonebook search/import/export  
Call history: dialed/received/missed/forwarded  
Black list

## IP-PBX Features

Busy Lamp Field (BLF), bridged Line Appearance (BLA)  
Anonymous call, anonymous call rejection  
Message Waiting Indicator (MWI), voice mail  
Call park, call pickup  
Intercom, paging  
Music on hold  
Hot-desking

## Display and Indicator

3.5" 480 x 320-pixel color display with backlight  
16 bit depth color  
LED for call and message waiting indication  
Dual-color (red or green) illuminated  
LEDs for line status information  
Wallpaper, national language selection  
Intuitive user interface with icons and soft keys  
Caller ID with name, number and photo

## Feature keys

8 line keys with LED  
8 line keys can be programmed up to  
28 various features (4-page view)  
8 feature keys: voice mail, headset, mute,  
speaker, conference, hold, transfer, redial  
4 context-sensitive "soft" keys  
6 navigation keys, volume control keys  
Illuminated speaker key/headset key/mute key

## Interface

Dual-port Gigabit Ethernet  
Power over Ethernet (IEEE 802.3af), class 3  
1xRJ9 (4P4C) handset port  
1xRJ9 (4P4C) headset port  
Supports up to 6 Expansion Modules

## Physical Features

Stand with 3 adjustable angles  
Wall mountable  
External universal AC adapter :  
AC 100~240V input and DC 5V/1.2A output  
Power consumption (PSU): 2.0~4.6W  
Power consumption (PoE): 2.5~5.5W  
Operating humidity: 10~95%  
Operating temperature: -10~50°C

## Management

Configuration: browser/LCD-Menu/auto-provision  
Auto provision via HTTP/HTTPS FTP/TFTP  
Auto-provision with PnP  
Reset to factory, restart, reboot  
Local tracing log export, system log  
Phone lock for personal privacy protection

## Network and Security

SIP v1 (RFC2543), v2 (RFC3261)  
SIP server/proxy redundancy  
NAT Traversal: STUN mode  
DHCP/static/PPPoE/IEEE802.1X/open VPN  
HTTP/HTTPS web server  
Time and date synchronization by SNTP  
DNS-NAPTR/DNS-SRV (RFC 3263)  
QoS: 802.1p/Q tagging (VLAN), Layer 3 ToS DSCP  
TLS (Transport Layer Security), SRTP, ZRTP  
HTTPS certificate manager  
AES encryption for configuration file  
Digest authentication using MD5/MD5-session  
IPv6 supported