

## Enterprise HD IP Phone---Classic IP Phone UC912

UC912 delivers superior HD audio quality, rich and leading edge telephony features, all the functions of software are the same as other UC900 series models. It is a perfect choice for small to medium businesses looking for a high quality, feature rich IP Phone at an affordable cost.

# UC912





## Phone Features

---

4 SIP accounts  
Call hold, mute, DND  
One-touch speed dial, hotline  
Call forward, call waiting, call transfer  
Redial, call return, auto answer, direct IP call  
5-way conferencing  
Group listening, SMS, emergency call  
Ring tone selection/provisioning  
Set date time automatically or manually  
Dial plan for each account  
RTCP-XR (RFC3611), VQ-RTCPXR (RFC6035)  
Action URL/UR

## Audio Features

---

HD Voice: HD Speaker, HD Handset, HD codec  
Codecs: iLBC, G.722, G.711(A/μ), Opus, G.723.1, G.729AB, G.726-32  
DTMF: In-band, RFC 2833, SIP INFO  
Full-duplex hands-free speakerphone with AEC  
AEC, VAD, AGC, CNG, PLC, AJB

## Directory

---

Local phonebook up to 1000 entries  
XML/LDAP remote phonebook  
Intelligent search method  
Phonebook search/import/export  
Call history: dialed/received/missed/forwarded  
Black list

## IP-PBX Features

---

Busy Lamp Field (BLF), bridged Line Appearance (BLA)  
Anonymous call, anonymous call rejection  
Message Waiting Indicator (MWI), voice mail  
Intercom, paging  
Hot-desking  
Call park, call pickup  
Music on hold

## Display and Indicator

---

192x64 pixel graphical LCD with backlight  
LED for call and message waiting indication  
Illuminated LEDs for line status information  
Intuitive user interface with icons and soft keys  
National language selection  
Caller ID with name, number

## Feature keys

---

4 line keys with LED  
4 line keys can be programmed up to 12  
Paperless DSS keys (4-page view)  
6 feature keys: voice mail, headset, mute speaker, transfer, redial  
4 context-sensitive "soft" keys  
6 Navigation keys (include cancel key) and volume control keys

## Interface

---

Dual-port 10/100M Ethernet  
Power over Ethernet (IEEE 802.3af), class 2  
1xRJ9 (4P4C) handset port  
1xRJ9 (4P4C) headset port

## Physical Features

---

Wall mountable  
Stand with 2 adjustable angles  
External universal AC adapter :  
AC 100~240V input and DC 5V/1.2A output  
Power consumption (PSU): 1.6~4.2W  
Power consumption (PoE): 2.1~5.1W  
Operating humidity: 10~95%  
Operating temperature: -10~50°C

## Management

---

Configuration: browser/LCD -Menu/auto -provision  
Auto provision via HTTP/HTTPS FTP/TFTP  
Auto -provision with PnP  
Reset to factory, restart, reboot  
Local tracing log export, system log  
Phone lock for personal privacy protection

## Network and Security

---

SIP v1 (RFC2543), v2 (RFC3261)  
SIP server/proxy redundancy  
NAT Traversal: STUN mode  
IP assignment: static/DHCP  
HTTP/HTTPS web server  
Time and date synchronization using SNTP  
DNS-NAPTR/DNS-SRV (RFC 3263)  
QoS: 802.1p/Q tagging (VLAN), Layer 3 ToS DSCP  
Transport Layer Security (TLS 1.2), SRTP, ZRTP  
HTTPS certificate manager  
AES encryption for configuration file  
Digest authentication using MD5/MD5-session  
IEEE 802.1X/OpenVPN  
IPv4/IPv6, LLDP/CDP/DHCP VLAN